

SmartCabinet™

Customer :


Abhishek Datta
Product Specialist

05.01.2018




Smart Solution Introduction

Conventional Data Center Components



SmartSolution Basic Broad Components




Data Centre as expected ...



Data Centre as built ...

Smart Solution Introduction



WHY DOES





IT HAPPEN!

Smart Solutions Portfolio

Rack Level

Row Level

Room Level



Capabilities:

- Simplification
- Standardization
- Speed

Benefits:

- Time
- Cost
- Risk

IS THERE A



ONE

SIZE FITS ALL
SOLUTION?

SmartCabinet™ Platform

Complete Modular Data Center Infrastructure

Supply Capabilities

Integrated with :

- UPS & Battery (Rack mounted up to 10kVA)
- Precision In-rack cooling DX, up to 7kW per rack
- 19" Server or Network rack (600 wide or 800 wide)
- Contained airflow, with emergency door opening
- Power distribution, system and rack level
- Monitoring, DCIM*, IPDUs*, KVM*
- Security system:
 - Access Control, Fire suppression & CCTV*
- Cable management

Services Capabilities

- White Glove Services
- Consolidated delivery
- Project management, assembly, installation & commissioning
- System-level documentation

Note: * Optional chargeable

SmartCabinet™



Self-contained, room-neutral design

- Simplifies deployment – reduces complexity of designing IT spaces from site to site
- Minimizes installation time – modular enclosure, power, & thermal management “building blocks”
- Enables standardization across sites

→ Simplification → Standardization → Speed

SmartCabinet™ Platform

UPS & Battery



Electrical Panel



RDU Monitoring



Vertical PDU



LCD & KVM




Biometric Access



IT Rack – 800 x 1000 x 42U,
Glass door



Rack Cooling Unit



Patented Containment Solution

Expansion Channels

- Containment modules that expand the rack enclosure to manage the system airflow
- Separate the IT equipment from the ambient air in the room
- Increase energy efficiency while reducing noise
- Factory assembled, simple mounting on site
- Easy to add future cabinets / capacity

Rear Channel (hot air)

- Hotter air to the cooling units = higher efficiency
- Emergency Door Opening provides unique level of protection

Front Channel (cold air)

- Ensures only conditioned air reaches IT equipment



Cold Air Side

UPS system is fully enclosed within the SmartRow™

- Batteries conditioned by cooling system

Rack-Mount UPS

- 10/20/30/40 kVA Rating models (10 - 1Ph & 20/30/40 – 3Ph)
- N + N Redundancy on system level
- Rack mount Battery modules
- 10 kVA – 2U, 20 kVA – 3U, 30/40 kVA - 4U
- Small size and high power density;
- Flexible output mode - 220/230/240Vac and 50/60Hz
- Highest Efficiency within its class up to 94.5%
- High system stability and intelligent control with DSP technology;
- Fan speed adjusting and fan fault auto-diagnosing;
- Three-level inverter technology improve efficiency;
- REPO for emergency;
- Display panel with both LCD and LED;
- 3 + 1 parallel (up to 20 kVA) & 1 + 1 parallel (30/40 kVA)



10kVA



20kVA



30/40kVA

LED panel



LCD panel



ON/SILENCE key

Monitoring Solution

RDU As an Aggregator

- Containment modules that expand the rack enclosure to manage the system airflow
- Separate the IT equipment from the ambient air in the




Intelligent Monitoring of UPS, Cooling & IPDUs (Optional)

- UPS – SNMP
- Cooling - SNMP
- IPDUs – Mention max qtys

SmartRow Environmental Monitoring

- TH Sensors –
- Smoke -
- WLD –
- Door –
- Mention max possible qtys



SmartSolution Management



Thailand



Malaysia



Singapore



Ahmedabad



Mumbai



Edge Network,
Pune



Regional DC,
Bangalore



RDU-M





Main DC,
Delhi




Fire Detection & Suppression

- 19" 3U Rack mount Fire Suppression system
- PESO Approved cylinders
- Novec 1230 Gas super pressurized with Nitrogen to 17 bar
- Seamless cylinders with capacities of
 - 1.5L (single rack)
 - 3L (Dual rack) inside 3U panel
- Discharge time 5-10 secs
- Pressure at Nozzle < 3 bar
- Discharge Flexi Hose with nozzles
- Power supply with battery back up
- Manual Release & Abort Switch
- Hooter for local alarm



Faster Deployment - Process Overview



Deployment Simplification

1. Arrives in a single delivery - complete
2. Brought into room
3. Equipment unpackaged & debris removed
4. System assembled & commissioned
 - Factory-integrated cabinets
 - Modular power & thermal management
5. On-site IP addressing, networking setup

Standardization

1. Maximum factory integration
2. Modular configurations enable simplicity & repeatability

Free up "Smart Hands"

1. Focus on IT hardware
2. Focus on application
3. Reduce time consumed by deployment

- Simplification
- Standardization
- Speed

Catalogue Models

Configuration	UPS Rating kVA	No of Racks	Usable "U" Space (Approx)	Inbuilt Back UP	UPS Redundancy (N+N)	Cooling Capacity (Kw)
SC-13-AC	3	1	23	5 Min	Yes	3.5 FS x 1
SC-26-AC	6	2	61	5 Min	Yes	3.5 FS x 2 nos
SC-210-AC	10	2	59	5 Min	Yes	7 FS x 1
SC-210-AC DS	10	2	59	5 Min	Yes	7 DS x 1
SC-210-RC	10	2	50	5 Min	Yes	7 FS x 2 nos
SC-210-RC DS	10	2	50	5 Min	Yes	7 DS x 2 nos

Cooling Options available:

0.5 TR

1TR

2TR FS & DS

1 TR TMM (Inverter Variable)

